

Grover's algorithm

Ashley Montanaro


School of Mathematics, University of Bristol
Bristol, UK

4 February 2019

Grover's algorithm alternates the operations $R_{|x_0\rangle}$ and $R_{|(+^n)^\perp\rangle}$, where $|(+^n)^\perp\rangle$ is a state orthogonal to $|+^n\rangle$ in the 2d space $\text{span}\{|x_0\rangle, |+^n\rangle\}$.


Grover's algorithm alternates the operations $R_{|x_0\rangle}$ and $R_{|(+^n)^\perp\rangle}$, where $|(+^n)^\perp\rangle$ is a state orthogonal to $|+^n\rangle$ in the 2d space $\text{span}\{|x_0\rangle, |+^n\rangle\}$.

The composition of two reflections is a rotation:



Grover's algorithm alternates the operations $R_{|x_0\rangle}$ and $R_{|(+^n)^\perp\rangle}$, where $|(+^n)^\perp\rangle$ is a state orthogonal to $|+^n\rangle$ in the 2d space $\text{span}\{|x_0\rangle, |+^n\rangle\}$.

The composition of two reflections is a rotation:



Grover's algorithm alternates the operations $R_{|x_0\rangle}$ and $R_{|(+^n)^\perp\rangle}$, where $|(+^n)^\perp\rangle$ is a state orthogonal to $|+^n\rangle$ in the 2d space $\text{span}\{|x_0\rangle, |+^n\rangle\}$.

The composition of two reflections is a rotation:

